QUALITY RENTAL TOOLS

TUBING SPECIFICATION SHEET

2 7/8" – 6.50 LBS/FT – L-80 – EUE 8RD – R2 - TUBING

TUBE / PIPE BODY	NOMINAL	
OD	2.875	in
ID	2.441	in
WEIGHT	6.50	lbs/ft
GRADE	L-80	
TUBE WALL	0.217	in
TUBING LENGTH	R2	

INSPECTION CLASS	PREMIUM	80%
RBW	0.174	in
TUBE TENSILE	114,076	lbs
TUBE COLLAPSE	8,006	psi
TUBE INTERNAL BURST	9,661	psi
TUBE TORSIONAL	6,754	ft-lbs

CONNECTION / TOOL JOINT	NOMINAL	
CONNECTION	2.875" EUE 8	RD
COUPLING OD	3.688	in
COUPLING ID	2.441	in
DRIFT	2.347	in
THREADS PER INCH	8	

TUBING ASSEMBLY	NOM	INAL
DISPLACEMENT ESTIMATE (INCLUDES TOOL JOINTS)	0.00236	bbls/ft
CAPACITY ESTIMATE (INCLUDES TOOL JOINTS)	0.00579	bbls/ft

	K	
MAKEUP TORQUE SPECIFICATIONS	NOM	INAL
THREAD COMPOUND FRICTION FACTOR	1.00	FF
MAXIMUM MAKEUP TORQUE	2,810	ft-lbs
MINIMUM MAKEUP TORQUE	1,690	ft-lbs

Information is provided for reference and illustration purposes only. It has been extracted from information available from the manufacturer and other public domain sources. Quality Rental Tools accepts no responsibility or liability to any party for the accuracy of the technical information provided or for any error, omission, or misstatement. The reader is fully responsible for the accuracy of all technical data and expected to make independent enquiry and to rely on their own skill and judgement in evaluating whether any product or equipment is suitable.

Start saving time and money today!

To order your 2 7/8", EUE 8rd Tubing for your offshore & land needs, or for further information, please contact:

Toll Free	T: 888-922-3449	
Houma, Louisiana	T: 985-851-3449	
Cadiz, Ohio	T: 330-205-2718	
Midland, Texas	T: 432-219-3400	
company@qualityrentaltools.com		
www.gualityrentaltoo	ls.com	