

**TUBING SPECIFICATION SHEET**

**2 7/8" – 7.90 LBS/FT – P-110 – (PH6 TYPE) – R2 - TUBING**

TUBE / PIPE BODY	NOMINAL	
OD	2.875	in
ID	2.323	in
WEIGHT	7.90	lbs/ft
GRADE	P-110	
TUBE WALL	0.276	in
TUBING LENGTH	R2	

INSPECTION CLASS	PREMIUM 80%	
RBW	0.221	in
TUBE TENSILE	194,100	lbs
TUBE COLLAPSE	16,085	psi
TUBE INTERNAL BURST	16,896	psi
TUBE TORSIONAL	11,005	ft-lbs

CONNECTION / TOOL JOINT	NOMINAL	
CONNECTION	2.875" (PH6 TYPE)	
COUPLING OD	3.438	in
COUPLING ID	2.265	in
DRIFT	2.229	in
CONNECTION TENSILE	248,000	lbs



TUBING ASSEMBLY	NOMINAL	
DISPLACEMENT ESTIMATE (INCLUDES TOOL JOINTS)	0.00291	bbls/ft
CAPACITY ESTIMATE (INCLUDES TOOL JOINTS)	0.00523	bbls/ft

MAKEUP TORQUE SPECIFICATIONS	NOMINAL	
THREAD COMPOUND FRICTION FACTOR	1.00	FF
MAXIMUM MAKEUP TORQUE	4,375	ft-lbs
MINIMUM MAKEUP TORQUE	3,500	ft-lbs

Information is provided for reference and illustration purposes only. It has been extracted from information available from the manufacturer and other public domain sources. Quality Rental Tools accepts no responsibility or liability to any party for the accuracy of the technical information provided or for any error, omission, or misstatement. The reader is fully responsible for the accuracy of all technical data and expected to make independent enquiry and to rely on their own skill and judgement in evaluating whether any product or equipment is suitable.

***Start saving time and money today!***

To order your 2 7/8", (PH6 type) Tubing for your offshore & land needs, or for further information, please contact:

Toll Free T: 888-922-3449  
 Houma, Louisiana T: 985-851-3449  
 Cadiz, Ohio T: 330-205-2718  
 Midland, Texas T: 432-219-3400  
 company@qualityrentaltools.com  
 www.qualityrentaltools.com