

TUBING SPECIFICATION SHEET

2 7/8" – 9.50 LBS/FT – P-110 w/ Hardband (PH6 TYPE) – R2

TUBE / PIPE BODY	NOMINAL
OD	2.875 in
ID	2.195 in
WEIGHT	9.50 lbs/ft
GRADE	P-110
TUBE WALL	0.340 in
TUBING LENGTH	R2

INSPECTION CLASS	PREMIUM 80%
RBW	0.272 in
TUBE TENSILE	231,890 lbs
TUBE COLLAPSE	19,680 psi
TUBE INTERNAL BURST	20,810 psi
TUBE TORSIONAL	12,540 ft-lbs

CONNECTION / TOOL JOINT	NOMINAL
CONNECTION	2.875" (PH6 Type)
COUPLING OD	3.625 in
COUPLING ID	2.130 in
DRIFT	2.101 in
CONNECTION TENSILE	231,890 lbs



TUBING ASSEMBLY	NOMINAL
DISPLACEMENT ESTIMATE (INCLUDES TOOL JOINTS)	0.00352 bbls/ft
CAPACITY ESTIMATE (INCLUDES TOOL JOINTS)	0.00467 bbls/ft

MAKEUP TORQUE SPECIFICATIONS	NOMINAL
THREAD COMPOUND FRICTION FACTOR	1.00 FF
MAXIMUM MAKEUP TORQUE	6,188 ft-lbs
MINIMUM MAKEUP TORQUE	5,500 ft-lbs

Information is provided for reference and illustration purposes only. It has been extracted from information available from the manufacturer and other public domain sources. Quality Rental Tools accepts no responsibility or liability to any party for the accuracy of the technical information provided or for any error, omission, or misstatement. The reader is fully responsible for the accuracy of all technical data and expected to make independent enquiry and to rely on their own skill and judgement in evaluating whether any product or equipment is suitable.

Start saving time and money today!

To order your 2 7/8", 9.50lb (PH6 type) Tubing for your offshore & land needs, or for further information, please contact:

Toll Free T: 888-922-3449
 Houma, Louisiana T: 985-851-3449
 Cadiz, Ohio T: 330-205-2718
 Midland, Texas T: 432-219-3400
 company@qualityrentaltools.com
 www.qualityrentaltools.com